

0211.00

Prot 800

**Special protective anti-rust and water repellent lubricant for semi-finished materials, (even after cutting and grinding operations), metal sheets, coils, agricultural or industrial tools, mechanical devices, external parts of engines, weapons, etc.
It can be applied by brush, spray or dipping.**

PAKELO PROT 800 is a mixture of highly refined mineral base oils blended with exclusive additives that increase antirust protection and improve water repellency.

PAKELO PROT 800 has a low pour point and an excellent fluidity at low temperatures for an easier application.

0211.00

Prot 800

Application fields

PAKELO PROT 800 is recommended in lubricating and preserving semi-finished materials, metal sheets, coils, agricultural or industrial tools, mechanical devices, external parts of engines, weapons, etc..

It is particularly effective in cases of storage of semi-finished materials after cutting and grinding operations, for short periods (at maximum 1 month).

The product does not form a persistent drying layer nor waxy film and can be easily removed; it does not allow a short-term outdoor storage under corrosive ambient conditions.

The product can be applied by brush, spray or direct dipping of surfaces to be treated.

Chemical-Physical Characteristics

Prot 800	Method analysis	Unit measure	Value
Density at 15°C	ASTM D1298	kg/l	0,890
Kinematic Viscosity at 40°C	ASTM D445	cSt	9,0
Pour Point	ASTM D97	°C	<-45
Flash Point (C.O.C.)	ASTM D92	°C	145

The data just above refer to average values and must not be understood as guaranteed characteristics.

This Technical Data Sheet has been carefully checked to guarantee complete and precise information. However, we do not take any responsibility in case of damages caused by any mistakes or omissions. Due to continual product research and development, the information contained herein is subject to change without notification.