

0166.16

UTTO Fluid 4 D

SAE 10W-30

Multifunction lubricant for hydraulic controls, hydraulic and hydrostatic transmissions, differentials, final drives and axles of machines also with wet brakes/clutches.

PAKELO UTTO FLUID 4 D SAE 10W-30 is a multifunction mineral based lubricant formulated with selected additives that guarantee to finished product great performance in **hydraulic systems, transmissions** and **axles** of machines also with **wet brakes/clutches**.

Furthermore the product is formulated with special **friction modifiers additives** that enable to remove the stick-slip phenomena, and thus noise ("squawk") and vibrations in applications where this phenomenon can disclose (self locking differentials and wet brakes/clutches).

Vibrations can be generated when the braking action is next to the stop of the vehicle. In the worst cases the noise can be detected during ordinary slowing down phases.

PAKELO UTTO FLUID 4 D SAE 10W-30 is suitable for all friction material types typically used in wet brakes/clutches and it is effective in particular with the use of sintered discs.

The product guarantees high performance both in transmissions, thanks to high EP (Extreme Pressure) properties, and in hydraulic systems. In this case it helps reducing sludge formation and avoiding wear, oxidation, rust and corrosion.

PAKELO UTTO FLUID 4 D SAE 10W-30 provides the following main properties:

- excellent EP (Extreme Pressure) performance for a great protection of gears;
- high thermal-oxidative stability;
- high protection against sludge, varnish and deposits even in case of transmissions working at very high temperatures;
- great detergent/dispersant properties;
- good protection against bearing corrosion;
- high compatibility with yellow metals sometimes present both in hydraulic and hydrostatic systems;
- high anti-rust, anti-wear and anti-foam characteristics;
- very good performance in hydraulic systems and "Powershift" transmissions;
- great reduction of stick-slip phenomena in transmissions and axles with wet brakes/clutches;
- good filterability in hydraulic systems.

0166.16

UTTO Fluid 4 D

SAE 10W-30

Application fields

PAKELO UTTO FLUID 4 D SAE 10W-30 is a multifunction lubricant recommended for hydraulic and hydrostatic transmissions, torque converters, "Powershift transmissions", automatic transmissions, power take offs, differentials, final drives, axles and hydraulic controls of modern industrial, agricultural and earth moving machines also with wet brakes/clutches.

The product is available in different Viscosity Grades.
For the correct choice please refer to Constructors Recommendations and ambient temperatures.

Performance levels

The additive package used has enabled, in the set Viscosity Grades, to overcome the following Specifications/Classifications: **API** GL-4, **AGCO** Powerfluid 821XL / Powerfluid 821, **AGCO** Whitefarm Q-1826, Q-1766, Q-1722, Q1766B, Q-1705, Q-1802, Type 55, **Allison** C4, **Caterpillar** TO-2, **John Deere** JDM J20A/B/C/D, J14B/C, J21A, JDT 303, **Massey Ferguson** CMS M1135 / CMS M1141 / CMS M1143 / CMS M1145, M1110, M1127A, M1127B, M1129A, **Case New Holland** CNH MAT 3505 (MS 1206/7/9) / CNH MAT 3525 (FNHA 2-C-201.00 - Ford M2C-134D) / CNH 3526 (FNHA 2-C-200.00), **Case** MS 1207, MS 1210, MS-1206, JIC 145, JIC 143, JIC 144, MS-1204, JIC 185, B-5, B-6 (INTERNATIONAL HARVESTER) SEMS 17001 (STEIGER), **Fendt**, **Ford** 134-A/B/C/D, FNHA 2-C-200, FNHA 2-C-200A, FNHA 2-C-201, ESN-M2C 41B - 43 - 48A/B - 53 A/B - 92A, **Landini**, **Komatsu / Komatsu Dresser** B-06-0001 /0002, **Kubota UDT** Fluid, **Valtra** G2-08 / G2-B10, **Volvo VCE VME** WB 101, **ZF** TE-ML 03E / 03F / 05F / 06K / 17E.

Approvals

ZF TE-ML 03E / 05F / 17E / 21F (App. ZF004769).

Chemical-Physical Characteristics

UTTO Fluid 4 D	Method analysis	Unit measure	Value SAE 10W-30
Density at 15°C	ASTM D1298	kg/l	0,877
Kinematic Viscosity at 40°C	ASTM D445	cSt	60,8
Kinematic Viscosity at 100°C	ASTM D445	cSt	10,1
Viscosity Index	ASTM D2270	-	154
C.C.S. Viscosity at -25°C	ASTM D5293	cP	6800
Flash Point (C.O.C.)	ASTM D92	°C	>220
Pour Point	ASTM D97	°C	-35

The data just above refer to average values and must not be understood as guaranteed characteristics.

This Technical Data Sheet has been carefully checked to guarantee complete and precise information. However, we do not take any responsibility in case of damages caused by any mistakes or omissions. Due to continual product research and development, the information contained herein is subject to change without notification.